

C € 0085



CERT

EU type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085CP0138

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	BALTUR S.p.A. Via Ferrarese, 10, I-44042 Cento (Ferrara)
Distributor <i>Vertreiber</i>	BALTUR S.p.A. Via Ferrarese, 10, I-44042 Cento (Ferrara)
Product Category <i>Produktart</i>	Burners for boilers: Gas-/Oil-burner combination (3505)
Product Description <i>Produktbezeichnung</i>	Gas-/Oil-burner combination in monobloc construction
Model <i>Modell</i>	TBML ... MC/ME/P
Countries of Destination <i>Bestimmungsländer</i>	AT, BE, BG, CH, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR
Test Reports <i>Prüfberichte</i>	type testing: GB 190 2018 B4 from 08.11.2018 (TRG) type testing: GB 222 2018 B2 from 08.11.2018 (TRG) type testing: GB 211 2018 B3 from 08.11.2018 (TRG) type testing: GB 244 - 248 2018 B2 from 08.11.2018 (TRG) type testing: GB 286 2018 B2 from 20.11.2018 (TRG) type testing: GB 287 2018 B2 from 20.11.2018 (TRG)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 676 (01.11.2008)
Date of Expiry / File No. <i>Ablaufdatum / AZ</i>	07.12.2028 / 18-0221-GEA

70028-04-A-DE

07.12.2018 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-01

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Elektrical Data 230/400 V AC, 50 Hz
Elektrische Daten

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
TBML 50 MC	heat input - natural gas (Hi): 98...514 kW heat input - LPG (Hi): 104...508 kW	supply pressure: 22,2...360 mbar (NPG); 19,5...360 mbar (LPG)
TBML 50 ME	heat input - natural gas (Hi): 98...521 kW heat input - LPG (Hi): 111...508 kW	supply pressure: 18,0...360 mbar (NPG); 19,0...360 mbar (LPG)
TBML 80 MC	heat input - LPG (Hi): 190...932 kW	supply pressure: 41,0...360 mbar (LPG)
TBML 80 ME	heat input - natural gas (Hi): 145...919 kW heat input - LPG (Hi): 190...932 kW	supply pressure: 30,4...360 mbar (NPG); 41,0...360 mbar (LPG)
TBML 120 MC	heat input - natural gas (Hi): 216...1210 kW heat input - LPG (Hi): 235...1282 kW	supply pressure: 18,6...360 mbar (NPG); 23,1...360 mbar (NPG)
TBML 120 ME	heat input - natural gas (Hi): 231...1261 kW heat input - LPG (Hi): 234...1293 kW	supply pressure: 16,6...360 mbar (NPG); 23,0...360 mbar (LPG)
TBML 160 MC	heat input - natural gas (Hi): 200...1697 kW	supply pressure: 39,4...350 mbar (NPG)
TBML 160 ME	heat input - natural gas (Hi): 250...1631 kW heat input - LPG (Hi): 317...1662 kW	supply pressure: 25,0...360 mbar (NPG); 41,8...360 mbar (LPG)
TBML 200 MC	heat input - natural gas (Hi): 243...1982 kW heat input - LPG (Hi): 260...1932 kW	supply pressure: 25,5...360 mbar (NPG); 20,9...360 mbar (LPG)
TBML 200 ME	heat input - natural gas (Hi): 240...2090 kW heat input - LPG (Hi): 261...1938 kW	supply pressure: 20,0...360 mbar (NPG); 21,0...360 mbar (LPG)
TBML 260 MC	heat input - natural gas (Hi): 394...2923 kW heat input - LPG (Hi): 469...3000 kW	supply pressure: 54,9...360 mbar (NPG); 57,6...360 mbar (LPG)
TBML 260 ME	heat input - natural gas (Hi): 391...2924 kW heat input - LPG (Hi): 465...2999 kW	supply pressure: 57,6...360 mbar (NPG); 58,0...360 mbar (LPG)
TBML 360 MC	heat input - natural gas (Hi): 362...3670 kW heat input - LPG (Hi): 412...3625 kW	supply pressure: 66,5...360 mbar (NPG); 80,6...360 mbar (LPG)
TBML 360 ME	heat input - natural gas (Hi): 439...3945 kW heat input - LPG (Hi): 427...3920 kW	supply pressure: 68,5...360 mbar (NPG); 99,6...360 mbar (LPG)
TBML 60 P	heat input - natural gas (Hi): 180...701 kW heat input - LPG (Hi): 185...692 kW	supply pressure: 25,9...360 mbar (NPG); 33,9...360 mbar (LPG)
TBML 90 P	heat input - natural gas (Hi): 368...982 kW heat input - LPG (Hi): 374...998 kW	supply pressure: 20,5...360 mbar (NPG); 23,0...360 mbar (LPG)
TBML 150 P	heat input - natural gas (Hi): 510...1591 kW heat input - LPG (Hi): 471...1576 kW	supply pressure: 29,1...360 mbar (NPG); 37,0...360 mbar (LPG)

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

Appliance categories and countries of destination:

AT, BE, BG, CH, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR: I12R3R